

# TRISCO

## Technische gegevens PVC gecoat doek Sioen

### B7119

<b>Fabric / Weefsel / Tissu / Gewebe</b>	100 % PES / 1100 dtex	
<b>Inlage / Inlage / insert / einfügen</b>	7 x 7	
<b>Coating / Coating / Revêtement / Lack</b>	PVC	
<b>Roll length / Rollengte / Longueur du rouleau / Rollengte</b>	mtr. 65	
<b>Width / Breedte / Largeur / Breite</b>	cm. 250	
<b>Total weight / Gewicht totaal / Poids total / Totalgewicht</b>	g/m <sup>2</sup> 630	DIN EN ISO 2286/2 1998
<b>Lacquering / Vernis / Lackierung</b>	1/1	
<b>Embossing / Kalandr / Calandre / Lackierung</b>	Glossy	
<b>Breaking strength Warp / Treksterkte Ketting / Résistance rupture Chaîne / Höchstzugkraft Kette</b>	Ketting 2500 N/5 cm	EN ISO 1421/1 1998
<b>Breaking strength Weft / Treksterkte Inslag / Résistance rupture Trame / Höchstzugkraft Schuss</b>	Inslag 1800 N/5 cm	EN ISO 1421/1 1998
<b>Tear strength Warp / Scheurweerstand Ketting / Résistance à la déchirure Chaîne / Weiterreisskraft Kette</b>	Ketting 250 N	DIN 53363 2003
<b>Tear strength Weft / Scheurweerstand Inslag / Résistance à la déchirure Trame / Weiterreisskraft Schuss</b>	Inslag 250 N	DIN 53363 2003
<b>Adhesion / Hechting / Adhérence / Haftung</b>	90 N/5 cm	EN ISO 2411 2000
<b>Temperature resistance / Temperatuursbestendigheid / Tenue à la température / Temperatuursbeständigkeit</b>	°C -30 / +70	DIN EN 1876/2 1998
<b>Light fastness (Except white and (half-)transparent) / Lichtechtheid (Uitgezonderd wit en (half-)transparent) / Tenue à la lumière (Excepté en blanc et (semi-)transparent) / Lichtechtheid (Ausnahme weiss und (semi-)transparent)</b>	7-8	ISO 105 B02 2014
<b>Fire behavior / Brandgedrag / Reaction au feu / Brennverhalten</b>	< 100 mm/ min	ISO 3795 1989

Application -> Truck/Flat Cover



# SIOEN

"This product may for certain colours contain substances (Lead Pigments) which fall under the Annex XIV of the Reach Regulation 1907/2006/CE. In order to know which colours fall under this annex, you can take contact with the technical department of Sioen Industries. Upon request those substances can be eliminated from the product."

# WWW.TRISCO.NL